

A800-M Dual Fingerprint Module

- ✓ FBI Certified: FBI IAFIS IQS Appendix F, Mobile ID FAP 45
- ✓ Live Finger Detection (LFD)
- ✓ AES-256 Encryption
- ✓ High Image Quality for Dual Finger Flats, Single Flats/Rolls



Tough. Reliable. Easily integrated. The Aratek A800-M fingerprint module is an FBI FAP 45 optical fingerprint sensor that supports highly accurate two-finger flats and single-finger flat/roll fingerprints acquisition. It fully meets the stringent requirements of the FBI Appendix F (Mobile ID FAP 45) standards on human fingerprint comparison. With easy integration into handhelds, mobile ID terminals, POS, kiosks and other devices, the A800-M is the perfect embedded solution for applications like National ID, Law Enforcement, Border control, Finance and Banking that require high-quality dual finger flat or single flat/roll fingerprints.

Features

- **FBI Appendix F FAP 45 Certified**
FBI Certified: FBI IAFIS IQS Appendix F, Mobile ID FAP 45
- **AES-256 Encryption**
256-bit AES encryption (AES-256) to ensure the security of your fingerprint data in transit
- **International Standards**
ISO19794-2, ISO19794-4, ANSI 378, ANSI 381, JPG2000, and WSQ supported.
- **Advanced Algorithm**
NIST MINEX III compliance Bione® fingerprint algorithm delivers the highest extracting and matching performance.
- **Comprehensive SDK**
Comprehensive software development kit is available for easy development and integration.
- **Live Finger Detection (LFD)**
Live Finger Detection technology to detect fake fingers.
- **Strong Adaption**
Excellent image quality for dry, moist and rough fingers.
- **Cloud Platform**
Seamlessly join in Aratek TrustLink™ biometrics authentication platform
- **Different OS Support**
Windows 7 / 8 / 10 / 2000 / XP / Vista, Linux, Android

Applications

- National ID
- Voter Registration
- e-Passport & Visa
- Law Enforcement
- Border control
- Finance and Banking

A800-M FAP 45 Dual Fingerprint Module

Physical Parameter

Dimension	64.0*62.0*36.5 mm (L*W*H)
Weight	124.0 g

Performance Parameter

Capture Mode	Optical Touch
Platen Size	39.0*41.0 mm
Sensing Area	38.10 mm*40.64 mm
Fingerprint Image Size	750*800 pixels
Image Resolution	500 dpi
Gray level	256 level

Communication Mode

Communication Interface	USB
-------------------------	-----

Operation Environment

Work Voltage	5.0 V
Work Current	≤200mA
Temperature	Working: -20°C ~55°C Storage: -40°C ~70°C
Humidity	10~93% R.H

Certification

CE, FCC, RoHS, FBI Appendix F (Mobile ID FAP 45)

Supported OS

Windows / Android / Linux / Others



Aratek Biometrics Co., Ltd.

10F, No. 131, Songjiang Road, Zhongshan District, Taipei City 10491, Taiwan

+886 2-2501-0001

sales@aratek.co

www.aratek.co

©Copyright 2021. Aratek Biometrics Co., Ltd.

Aratek logo is a registered trademark of Aratek or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademark of their respective owners.

All specifications are subject to change without notice. All rights reserved.