

## Standard Features include:

- Polypropylene, TPR and EPDM construction - chemical resistant.
- Large number of Ezi-action® Adaptor Fittings - covers all drum and container thread configuration.
- Ezi-action® Adaptor Fittings slide up and down the shaft - pump sits on the base of the drum or container.
- Hand tightening will secure the pump to the drum or container - no tools required.

Technical Data				
Style	Fitting	Fitting	Parts	Material of construction
Drums	MR	40 litre to 215 litre (10 gallon to 55 gallon) 1000 litre (220 gallon)	Locking ring Thread connection Locking seal	Polypropylene Polypropylene TPR
	MBSP			
	MBSP55			
	M55			
	M63, M63B			
	M63R			
	M69			
Container	C63 (Int)	5 litre* to 30 litre (1 gallon* to 8 gallon) *Container opening needs to be greater than 45mm	Thread connection Locking ring O Ring	Polypropylene Polypropylene EPDM / Buna
	C55			
	C69 (USA)			
	C57 (Eng)			
	C English Metal			
	C Australian Metal			
	PSA (Pour Spout Adaptor)			
	C63NZ			
	C65			
	C69NZ			



CAM



C55



C57



C69NZ



C69



C63



PSA



M55



C63N



CEM



MBSP



MR



M63



M69



MBSP55



M63R

## How can the correct M adaptor fitting for drums be determined?

Nine different thread options including a Flexi Pour Spout Adaptor (PSA) cater for the many different thread styles from around the world. To determine the thread for containers measure the internal diameter of the container cap thread and describe the thickness of the thread and if necessary for further differentiation the shape of the thread.

Ezi-action® C fittings	Description
C55	55mm internal diameter with medium thread
C63Int	63mm internal diameter with medium thread and flat edge
C63 NZ	63mm internal diameter with medium thread and flat edge
Australian Metal	for metal containers 55mm internal diameter with fine/medium thread
C57 English	57mm internal diameter with coarse thread
English Metal	56mm internal diameter with fine thread
C69 NZ	69mm internal diameter with coarse thread
C69 USA	69mm internal diameter with medium thread
Flexi Pour Spout Adaptor (PSA)	Replaces the Flexi pour spout or can be inserted into a 71mm diameter hole cut into a container lid. (Instructions provided)
C65	65mm internal diameter with coarse thread



C69



PSA

## How can the correct M adaptor fitting for drums be determined?

Six different thread options cater for the many different thread styles from around the world. To determine the Ezi-action® adaptor fitting required for drums measure the outside diameter of the thread portion of the bung and describe the thickness of the thread.

Ezi-action® M fittings	Description
MBSP	55mm outside diameter with fine thread (Usual fitting on metal drums)
MBSP55	For a British standard fine thread (58mm outside diameter of bung) or a 56 x 4 buttress opening
M55	55mm outside diameter with medium thread. Also known as Trisure, BCS, Mauser and coarse 56 x 4 buttress
M63	63mm outside diameter with coarse thread
M69	69mm outside diameter with coarse thread
MR	55mm outside diameter with fine thread (11 rings compared with the 10 rings on the MBSP)
M63B	63mm outside diameter with slightly coarser thread than M63
M63R	For a rieke fine thread (55mm outside diameter of bung) or into a drum with a coarse thread (63mm outside diameter of bung)



MR



M63