

ONEFLEX™

FIBERGLASS INSULATED FLEXIBLE DUCT





ONEFLEX™

- 25ft R6/R8 Duct
- Owens Corning Fiberglass
- STANDARD
 - ISO9001
 - UL181
- FIRE RESISTENT
- 2"-42" Available
- Production Capability
 - 24,000m/day (current)
- Delivered Cost: Retail
 - 1:5 (bagged)

R8 DUCT SIZE	LENGTH	L	W	H	VOL
4	25 FT	0.22	0.22	1	0.0484
5	25 FT	0.25	0.25	1	0.0625
6	25 FT	0.27	0.27	1	0.0729
7	25 FT	0.3	0.3	1	0.09
8	25 FT	0.32	0.32	1	0.1024
9	25 FT	0.35	0.35	1	0.1225
10	25 FT	0.37	0.37	1	0.1369
12	25 FT	0.42	0.42	1	0.1764
14	25 FT	0.47	0.47	1	0.2209
16	25 FT	0.52	0.52	1	0.2704
18	25 FT	0.57	0.57	1	0.3249
R6 DUCT SIZE	LENGTH	L	W	H	VOL
4	25 FT	0.18	0.18	0.81	0.026244
5	25 FT	0.21	0.21	0.81	0.035721
6	25 FT	0.23	0.23	0.81	0.042849
7	25 FT	0.26	0.26	0.81	0.054756
8	25 FT	0.28	0.28	0.81	0.063504
9	25 FT	0.31	0.31	0.81	0.077841
10	25 FT	0.33	0.33	0.81	0.088209
12	25 FT	0.38	0.38	0.81	0.116964
14	25 FT	0.43	0.43	0.81	0.149769
16	25 FT	0.48	0.48	0.81	0.186624
18	25 FT	0.53	0.53	0.81	0.227529

*MFR to provide update to match new compression standard

